

Amendments to the Claims:

Kindly cancel claims 7-21, 24, 27 and 29 without prejudice.

Kindly amend claim 1, 22, 23, 25, 26 and 28 as follows.

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An apparatus for generating and feeding moisture, comprising:

a reactor having an upstream gas inlet side, a downstream moisture outlet side and a catalyst for generating moisture from hydrogen and oxygen, wherein the reactor generates moisture from hydrogen and oxygen by catalytic reaction at a temperature of not higher than 450°C;

means for reducing pressure provided on the downstream side of the reactor, and disposed so that moisture leaving and fed from said reactor is reduced in pressure by the means for reducing pressure while an internal high pressure in the reactor is maintained, wherein the means for reducing pressure comprises one or more components selected from the group consisting of an orifice, a valve, a capillary and a filter;

a first reactor structural component having a material gas supply joint defining a material gas supply passage;

a second reactor structural component having a moisture gas take-out joint defining a moisture outlet passage, wherein the second reactor structural component is dimensioned to have a first diameter, wherein the first reactor structural component and the second

reactor structural component are mated to form a reactor shell having an interior space, and wherein the second reactor structural component defines an inside wall surface;

a first reflector disposed in the interior space to face the material gas supply passage;

a second reflector disposed in the interior space to face the moisture outlet passage, wherein the first reflector and the second reflector are identical flat plates symmetrically disposed in the interior space, the first reflector and the second reflector each include a peripheral portion inclined in cross-section, and the second reflector includes a dimension exceeding one half the first diameter of the second reactor structural component; wherein the catalyst comprises a platinum coated catalyst layer provided on the inside wall surface of the second reactor structural component; and

a process chamber, wherein the reactor is connected to feed moisture gas to the process chamber, wherein the moisture gas fed into the process chamber is reduced in pressure by the means for reducing pressure.

Claims 2-21 are canceled.

22. (Currently Amended) An apparatus for generating and feeding moisture according to claim 21, wherein internal pressure within the process chamber is 1-100 Torr.

23. (Currently Amended) An apparatus for generating and feeding moisture, comprising:

a reactor having an upstream gas inlet side, a downstream moisture outlet side and a catalyst for generating moisture from hydrogen and oxygen, wherein the reactor generates moisture from hydrogen and oxygen by catalytic reaction at a temperature of not higher than 450°C;

means for reducing pressure provided on the downstream side of the reactor, and disposed so that moisture leaving and fed from said reactor is reduced in pressure by the means for reducing pressure while an internal high pressure in the reactor is maintained, wherein the means for reducing pressure comprises one or more components selected from the group consisting of an orifice, a valve, a capillary and a filter;

a first reactor structural component having a material gas supply joint defining a material gas supply passage;

a second reactor structural component having a moisture gas take-out joint defining a moisture outlet passage, wherein the first structural component and the second structural component are mated to form a reactor shell having an interior space, wherein the interior space is dimensioned to provide a first distance separating the material gas supply passage and the moisture outlet passage, and wherein the second component defines an inside wall surface;

a reflector disposed in the interior space, wherein the reflector is a thick plate and includes a peripheral portion inclined in cross-section, wherein the plate has a thickness exceeding one half of the first distance; wherein the catalyst comprises a platinum coated catalyst layer provided on the inside wall surface of the second reactor structural component; and

a process chamber, wherein the reactor is connected to feed moisture gas to the

process chamber, wherein the moisture gas fed into the process chamber is reduced in pressure by the means for reducing pressure.

24. (Canceled)

25. (Currently Amended) An apparatus for generating and feeding moisture according to claim 234, wherein internal pressure within the process chamber is 1-100 Torr.

26. (Currently Amended) An apparatus for generating and feeding moisture, comprising:

a reactor having an upstream gas inlet side, a downstream moisture outlet side and a catalyst for generating moisture from hydrogen and oxygen, wherein the reactor generates moisture from hydrogen and oxygen by catalytic reaction at a temperature set in the range of 300°C to 450°C;

means for reducing pressure provided on the downstream side of the reactor, and disposed so that moisture leaving and fed from said reactor is reduced in pressure by the means for reducing pressure while an internal high pressure in the reactor is maintained, wherein the means for reducing pressure comprises one or more components selected from the group consisting of an orifice, a valve, a capillary and a filter;

a first reactor structural component having a material gas supply joint defining a material gas supply passage;

a second reactor structural component having a moisture gas take-out joint defining

a moisture outlet passage, wherein the first structural component and the second structural component are mated to form a reactor shell having an interior space, wherein the interior space is dimensioned to provide a first distance separating the material gas supply passage and the moisture outlet passage, and wherein the second component defines an inside wall surface;

a first reflector disposed in the interior space, wherein the first reflector is a thick plate that includes a peripheral portion inclined in cross-section and a thickness exceeding one half of the first distance; wherein the catalyst comprises a platinum coated catalyst layer provided on the inside wall surface of the second reactor structural component; and

a process chamber, wherein the reactor is connected to feed moisture gas to the process chamber, wherein the moisture gas fed into the process chamber is reduced in pressure by the means for reducing pressure.

27. (Canceled)

28. (Currently Amended) An apparatus for generating and feeding moisture according to claim 26, further comprising:

a reactor having an upstream gas inlet side, a downstream moisture outlet side and a catalyst for generating moisture from hydrogen and oxygen, wherein the reactor generates moisture from hydrogen and oxygen by catalytic reaction at a temperature set in the range of 300°C to 450°C;

means for reducing pressure provided on the downstream side of the reactor, and disposed so that moisture leaving and fed from said reactor is reduced in pressure by the

means for reducing pressure while an internal high pressure in the reactor is maintained, wherein the means for reducing pressure comprises one or more components selected from the group consisting of an orifice, a valve, a capillary and a filter;

a first reactor structural component having a material gas supply joint defining a material gas supply passage;

a second reactor structural component having a moisture gas take-out joint defining a moisture outlet passage, wherein the second reactor structural component is dimensioned to have a first diameter, and wherein the first structural component and the second structural component are mated to form a reactor shell having an interior space, and the second structural component defines an inside wall surface;

a first reflector disposed in the interior space;

a second reflector disposed in the internal space to face the moisture outlet passage, wherein the first reflector is disposed in the internal space to face the material gas supply passage, and the first reflector and the second reflector are identical flat plates symmetrically disposed in the interior space, the first reflector and the second reflector each include a peripheral portion inclined in cross-section, and the second reflector includes a dimension exceeding one half the diameter of the second reactor structural component; wherein the catalyst comprises a platinum coated catalyst layer provided on the inside wall surface of the second reactor structural component; and

a process chamber, wherein the reactor is connected to feed moisture gas to the process chamber, wherein the moisture gas fed into the process chamber is reduced in pressure by the means for reducing pressure.

29. (Canceled)

30. (Previously Presented) An apparatus for generating and feeding moisture according to claim 26, wherein internal pressure within the process chamber is 1-100 Torr.

31. (Previously Presented) An apparatus for generating and feeding moisture according to claim 26, wherein the set catalytic reaction temperature is selected from the group consisting of 300°C, 350°C and 400°C.

32. (Previously Presented) An apparatus for generating and feeding moisture according to claim 26, wherein a temperature difference between the set temperature and an ignition point of hydrogen is set between 190°C and 230°C.

33. (Previously Presented) An apparatus for generating and feeding moisture according to claim 32, wherein the apparatus generates moisture at a rate of 2000 cc/minute.